



**Features**

F.A.T. Frequency Adapting Technology fires ALL single-ended (SE) and double-ended (DE) lamps including high-frequency DE lamps

MH/HPS switchable up to 1000 watts

Generator ready

Delayed ignition stabilizes start-up loads and extends lamp life

Four (4) switchable wattage settings (400W SE, 600W SE, 1000W SE, 1000W DE)

LED status/wattage indicators

Built-in fan for cooling

6' power cord provided

UL listed for safety

120/208/240/277VAC voltage sensing input

3 year warranty

**Protections**

- |                  |                        |
|------------------|------------------------|
| Short circuit    | Open circuit           |
| Ignition failure | End of Lamp Life (EOL) |
| Overheat         | Soft-start             |
| Over voltage     | Low voltage            |
| Fan failure      |                        |

**Performance**

Rated Voltage: AC90-305VAC

Input Frequency: 50/60Hz

Ambient operating temperature (TA): -40°C ~ 50°C

Crest Factor (CF): <1.5

Power Factor (PF): ≥0.99

Total Harmonic Distortion (THD): <10%

Current draw: 8.6A @ 120VAC, 4.1A @ 240VAC, 3.8A @ 277VAC

Dimensions L 15.75"x W 4.53"x H 2.95"

Weight: 7.72 lbs / 4kg

Item No. GLB-1000-DE-120/277

