



### Features

F.A.T. Frequency Adapting Technology fires ALL single-ended (SE) and double-ended (DE) lamps including high-frequency DE lamps

MH/HPS switchable up to 1000 Watts

Generator ready

Delayed ignition stabilizes start-up loads and extends lamp life

Four (4) switchable wattage settings (400W SE, 600W SE, 1000W SE, 1000W DE)

LED status/wattage indicators

Built-in fan for cooling

6' power cord provided

UL Listed for safety

120/208/240/277VAC voltage sensing input

Three (3) year warranty

### Protections

Short circuit

Open circuit

Ignition failure

End of Lamp Life (EOL)

Overheat

Soft-start

Over voltage

Low voltage

Fan failure

### Performance

Rated Voltage: AC90-305VAC

Input Frequency: 50/60Hz

Ambient Operating Temperature (TA): -40°C ~ 50°C

Crest Factor (CF): <1.5

Power Factor (PF): ≥0.99

Total Harmonic Distortion (THD): <10%

Current Draw: 8.6A @ 120VAC, 4.1A @ 240VAC, 3.8A @ 277VAC

Dimensions L 15.75" x W 4.53" x H 2.95"

Packaged Weight:  
7.4lbs/3.34kgs

Installed Weight:  
6.6lbs/2.99kgs

Item No. GLB-1000-DE-120/277

