

IMPORTANT SAFEGUARDS READ CAREFULLY AND FOLLOW ALL SAFETY INSTRUCTIONS.

When using electrical equipment, basic safety precautions should always be followed including the following:

- DISCONNECT AC POWER SUPPLY BEFORE SERVICING.
- Installation and servicing of this equipment should be performed by qualified service personnel only.
- Ensure the electrical connections conform to the National Electrical Code and local regulations if applicable.
- Do not mount near gas or electrical heaters.
- Equipment should be mounted in locations and at heights where it will not readily be subjected to tampering by unauthorized personnel.
- The use of accessory equipment not recommended by the manufacturer may cause an unsafe condition. Any modification or use of non-original components will void the warranty and product liability.
- Do not use this equipment for other than intended use.
- Protect fixture from direct contact with all liquids to avoid breakage and/or thermal shock.
- Do not exceed maximum fixture voltage of 600V.
- Do not turn lamp on until fixture and ballast are properly installed.
- Make sure fixture is properly supported (fixture weight 6.6 lbs).
- Allow lamp to cool before handling.
- Do not use excessive force when installing lamps in fixture.
- Properly dispose of all lamps in properly rated container.
- Wear safety glasses and gloves when installing lamps.
- Under normal operating conditions, fixture may become hot.
- Keep fixture away from all flammable material.
- Do not mount fixture directly touching and surface.
- Do not pull the cord to unplug the fixture, pull on the plug only.
- Do no lift fixture by the cord.
- Always wear protective eye wear around the fixture. Looking directly into fixture may be harmful to your eyes.
- Replace removable parts after servicing.

SAVE THESE INSTRUCTIONS!

BOX CONTENTS:

- (1)pc HSE-E reflector unit (weight 6.6 lbs.) (A)
- (1)pc Fine hammertone reflector (B)
- (1)pc Removable universal ballast bracket (C)
- (1)pc 15' lamp extension cord. (D)
- (1)pc Eye bolt (E)
- (2)pcs Thumbscrews (F)
- (2)pcs V-Hooks (G)



In order to maintain a safe installation:

Ensure a minimum mounting clearance on all sides of 6".
 Ensure ventilation/cooling system can maintain an ambient air temperature below 95°F/203°C.
 Use ballast and lamp combination with ratings 315/1000W, 600V max where the maximum wattage does not exceed 1000W and the lamp type is metal halide or high pressure sodium.
 Keep protective barrier in place. Keep lamp cord away from housing.

CAUTION - To avoid UV exposure risk, use ANSI Type ("O") lamp only. Do not install a lamp that requires UV filtering.

Lamp/Re-Lamp Requirements

WATTAGE	ANSI
315	C182/O
1000	S52

Suitable for damp locations.

When choosing to use removable universal ballast bracket (C), attach rope ratchets (not included) or Jack Link Chain (not included) directly to eye bolt (E) for mounting.

Install V-hooks (G) into the two holes on the end of the fixture on both sides if choosing not to use removable universal ballast bracket for mounting.

