

Model:	Date:
Accessories:	
Job Name:	Туре:

# GERMINATOR

40W 4' Linear Vaportight LED

## FEATURES

- •40W Full-spectrum LED for clones and germination
- · Low profile ideal for vertical grows
- Full-spectrum white LEDs outperform T5 fluorescents
- Precision optical lens efficiently delivers light to the plant canopy
  IP65 rated making it ideal for multi-level growing environments in wet locations
- 6' 120VAC Line cord with plug
- 120-277VAC Input
- UL Listed
- Five Year Warranty (Terms and Conditions Apply)


#### SPECIFICATIONS

Light Uniformity (avg/min)*:	1.82
Light Uniformity (max/min)*:	2.64
PPFD Avg (400-700nm)*:	66 µmol/m²/s
<b>PPFD Max</b> (400-700nm)*:	96 µmol/m²/s
<b>PPFD Min</b> (400-700nm)*:	37 µmol/m²/s
Lumens:	4147 lm
Color Temperature (CCT):	5000K
CRI:	≥ 80
Mounting Height above Canopy:	6" to 12"
Coverage Area:	2' x 4'
Typical Power Consumption:	40W
Input Voltage:	120-277VAC
Operating Frequency:	50/60Hz
Operating Temperature:	-20°C to 40°C (-4°F to 104°F)
Dimming:	N/A
Environment:	IP65, UL Listed for Wet Locations
Power Factor:	≥ .99
Lifetime Rating (L70):	50,000 hrs
Certifications:	cULus
Warranty:	5 Years

**\*NOTE:** All measurements taken at 12" above canopy.










w

Mounting Clip Detail





# DIMENSIONS Series L

GRM-40L-WH	47.2"	3.3"	2.1"


### WEIGHT

Series	Packaged Weight	Installed Weight
GRM-40L-WH	6.3 lbs (2.8kgs)	5.5 lbs (2.5kgs)

#### **ORDERING INFORMATION**

#### Example: GRM-40L-WH


Series/Configuration	Description	
GRM-40L-WH	40W 4' Linear vaportight LED, full-spectrum, 120-277VAC, wet location, white finish	






н

#### LIGHT DISTRIBUTION PERFORMANCE



Mounting height varies depending on the application.





7885 North Glen Harbor Blvd Glendale, Arizona 85307 800.533.3948 barronltg.com